

M40 圆形电源连接器

现场接线
3+PE+2针
3+PE+4针



插针 延长式

1 型号		No.	M40-6MS.P-DL	M40-8MS.P-DL															
极数			6p(4xφ3.6+2xφ2)	8p(4xφ3.6+4xφ2)															
电缆出线直径			13-28mm	13-28mm															
针脚排序																			
2 技术参数																			
额定电压		630V (AC/DC) / 250V (AC/DC)																	
额定电流		55A/28A																	
防护等级		IP67-插孔插针配合拧紧																	
温度范围		-20...+130℃																	
测试电压(两插针之间)		4000V/2500V																	
外壳材料		锌合金压铸件 黄铜, 镀镍																	
绝缘内嵌体材料		PA66/PBT,UL 94/V0																	
接触件 (插针/插孔)		 <table border="1" data-bbox="790 1500 1220 1691"> <thead> <tr> <th>类型</th> <th>压线范围</th> <th>订货号</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插针 Ø 2 mm</td> <td>1.0-2.5mm²</td> <td>EDF2-2.5</td> </tr> <tr> <td>2.5-4.0mm²</td> <td>EDF2-4.0</td> </tr> <tr> <td rowspan="3">插针 Ø 3.6mm</td> <td>1.5-4.0mm²</td> <td>EDF36-4.0</td> </tr> <tr> <td>4.0-6.0mm²</td> <td>EDF36-6.0</td> </tr> <tr> <td>6.0-10.0mm²</td> <td>EDF36-10.0</td> </tr> </tbody> </table>			类型	压线范围	订货号	插针 Ø 2 mm	1.0-2.5mm ²	EDF2-2.5	2.5-4.0mm ²	EDF2-4.0	插针 Ø 3.6mm	1.5-4.0mm ²	EDF36-4.0	4.0-6.0mm ²	EDF36-6.0	6.0-10.0mm ²	EDF36-10.0
类型	压线范围	订货号																	
插针 Ø 2 mm	1.0-2.5mm ²	EDF2-2.5																	
	2.5-4.0mm ²	EDF2-4.0																	
插针 Ø 3.6mm	1.5-4.0mm ²	EDF36-4.0																	
	4.0-6.0mm ²	EDF36-6.0																	
	6.0-10.0mm ²	EDF36-10.0																	
订货号																			
订货范例	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; width: 150px; height: 20px;"></div> <div style="border: 1px solid black; width: 150px; height: 20px;"></div> <div style="border: 1px solid black; width: 150px; height: 20px;"></div> </div>																		
	1	2	3																
	连接器类型	电缆线号	电缆长度																
订货型号的第二部分和第三部分可根据线号和长度不同自行修改, 电缆长度单位: M (米)																			